



XIBELIS TELULINK

HIGH TECH, LOW COST, AND EASY COMMUNICATION EQUIPMENT THAT ALLOWS YOU
TO MAKE GSM MOBILE NETWORK CALLS FROM ANALOG TELEPHONES OR PBX.

XIBELIS TELULINK

APPLICATIONS

PBAX; COST REDUCTION TO MAKE CELL PHONE CALLS
TELEPHONE BOOTHS / CALL CENTERS
PUBLIC TELEPHONY

SPECIAL FEATURES

POLARITY INVERSION
ECHO CANCELLATION
DIALING RULES
CALL LENGTH LIMITATIONS
BLOCK INCOMING CALLS
QUICK DIALING (USE PREFIXES)
ELECTRONIC PADLOCK
CALL FORWARDING
CALLER ID
VOICEMAIL



PBAX



PUBLIC TELEPHONE

TECHNICAL SPECIFICATIONS XIBELIS TELULINK

POWER

VOLTAGE	12VDC
RATED POWER	0,96 W
MAXIMUM POWER	1,44 W

GSM

BANDS	850/900/1800/1900
SIMCARD	1
ANTENNA •	SMA FEMALE 50 OHM
CSD ••	HASTA 14.400 BPS
GPRS ••	CLASS 10
MS	CLASS B

PHYSICAL FEATURES

ENCAPSULATED	PLASTIC ABS
SIZE	159MM X 145MM X 40MM
WEIGHT	200G
TEMPERATURE	0 ~ +45 °C
HUMIDITY	5% ~ 95% NON CONDENSED

TELEPHONE INTERFACE

FXS LINES	1
CONNECTOR	RJ-11
LINE VOLTAGE	-48 V
LINE CURRENT	21 MA
REN NUMBER	3 REN A 200M
SHORTCIRCUIT PROTECTION	YES

USER INTERFACE

ANTENNA LEVEL	3 LED
STATUS	1 TWO-COLOUR LED
TELEPHONE LINE	1 LED
DATA ••	1 LED

OTHER FEATURES

PROGRAMMING BY DTMF
ANTENNA LEVEL FOR INSTALLATION
SIMLOCK
NETWORKLOCK

- INCLUDES EXTERNAL MAGNETIC BASE ANTENNAS OF 3 DBI
- AVAILABLE IN THE TELULINK DATA VERSION